

**ODH150 OIL DELIVERY HOSE ท่อส่งน้ำมัน**

**RECOMMEND FOR OIL, HYDRALIC AND PETROLEUM BASED FLUID**

**DELIVERY WITH UP 55% AROMATIC CONTENT.**



- Tube** : Black, smooth conductive NBR compound.  
**Reinforcement** : Synthetic, high tensile strenght textile with anti-static copper wires.  
**Cover** : Black wrapped finish. Excellent resistance to oil and weather.  
**Temperature** : -20°C to+ 80°C  
**Branding** : OD10-(size) OIL DELIVERY HOSE ID (size) W.P.150PSI B.P.450PSI  
**Brand Type** : Bright orange negative branding on black cover.

| PART NO   | I.D.  |       | O.D.  |       | Max.Working           | Min.Burst      |
|-----------|-------|-------|-------|-------|-----------------------|----------------|
|           | inch  | mm    | inch  | mm    | bar<br>Pressure (psi) | Pressure (bar) |
| ODH150-20 | 1 1/4 | 32.0  | 1.732 | 44.0  | 150                   | 450            |
| ODH150-22 | 1 3/8 | 35.0  | 1.811 | 46.0  | 150                   | 450            |
| ODH150-24 | 1 1/2 | 38.0  | 1.969 | 50.0  | 150                   | 450            |
| ODH150-26 | 1 5/8 | 41.3  | 2.087 | 53.0  | 150                   | 450            |
| ODH150-28 | 1 3/4 | 44.5  | 2.205 | 56.0  | 150                   | 450            |
| ODH150-32 | 2     | 51.0  | 2.480 | 63.0  | 150                   | 450            |
| ODH150-36 | 2 1/4 | 57.2  | 2.756 | 70.0  | 150                   | 450            |
| ODH150-38 | 2 3/8 | 60.3  | 2.835 | 72.0  | 150                   | 450            |
| ODH150-40 | 2 1/2 | 63.0  | 2.913 | 74.0  | 150                   | 450            |
| ODH150-44 | 2 3/4 | 69.9  | 3.268 | 83.0  | 150                   | 450            |
| ODH150-48 | 3     | 76.0  | 3.504 | 89.0  | 150                   | 450            |
| ODH150-64 | 4     | 102.0 | 4.646 | 118.0 | 150                   | 450            |

**หมายเหตุ : ราคาที่เสนอยังไม่รวมภาษีมูลค่าเพิ่ม 7%**