

OSH10 OIL SUCTION AND DELIVERY HOSE ท่อดูดน้ำมัน

RECOMMEND FOR OIL, HYDRALIC AND PETROLEUM BASED FLUID

DELIVERY WITH UP 55% AROMATIC CONTENT.



- Tube** : Black, smooth conductive NBR compound.
- Reinforcement** : Synthetic, high tensile strenght textile with anti-static copper wires.
- Cover** : Black wrapped finish. Excellent resistance to oil and weather.
- Temperature** : -20°C to+ 80°C
- Branding** : OD10-(size) OIL SUCTION/DELIVERY HOSE ID (size) W.P.150PSI B.P.450PSI
- Brand Type** : Bright orange negative branding on black cover.

PART NO	I.D.		O.D.		Max.Working Pressure (psi)	Min.Burst Pressure (bar)
	inch	mm	inch	mm		
OSH10-12	3/4"	19.0	1.142	29.0	150	450
OSH10-16	1"	25.0	1.378	35.0	150	450
OSH10-20	1.1/4"	32.0	1.693	43.0	150	450
OSH10-22	1.3/8"	35.0	1.811	46.0	150	450
OSH10-24	1.1/2"	38.0	1.969	50.0	150	450
OSH10-32	2"	50.0	2.480	63.0	150	450
OSH10-40	2.1/2"	63.0	3.031	77.0	150	450
OSH10-48	3"	76.0	3.583	91.0	150	450
OSH10-64	4"	102.0	4.685	119.0	150	450
OSH10-80	5"	127.0	5.787	147.0	150	450
OSH10-96	6"	152.0	6.850	174.0	150	450
OSH10-128	8"	203.0	8.976	228.0	150	450